



40 PGIR

- Being replaced with 40RM
- Fits all TH-75 and TH-75E
- Grease lubricate and adjustable Chevron packing
- Full 3" fluid passage
- Available wear tube

TECHNICAL

LENGTH	WIDTH	WEIGHT	HOSE CONN.	LOWER CONN.	FLUID PASSAGE	WORKING PRESSURE			
40 1⁄2	8 15/16	280	3" NPT	3 ½ IF (MOD)	3"	TO 1500 PSI			

WEIGHT CAPACITY

STATIC	ROTATING				
140,000 LBS	71,000 LBS @ 100 RPM				
,					

PARTS LIST

PART NUMBER	NAME	QTY. REQ.	
40PGIR-6000-XX	WESTERN SWIVEL, FOR TH-75 DRILL, 3" NPT H/C, STRAIGHT UP, (2) 2" OD TRUNNION PINS ON 8 15/16" SHOULDERS, WITH 3 ½" IF (MOD) LH PIN LOWER CONNECTION LH PIN LOWER CONNECTION		
40PGIR-04RM	GOOSENECK, 3" NPT FEMALE		
40PG-07	HOUSING SEAL	3	
40PGIR-08 SN	SPINDLE NUT, (NEW STYLE)	1	
40PGIR-08 SN-A	SET SCREW, SPINDLE NUT	2	
30WX-09	SHIELD SEAL	1	
30WX-10	BEARING SHIELD	1	
5JW-11	BEARING RETAINER WIRE	1	
5JW-12	BEARING	5	
40PG-14A	BEARING HOUSING, 2" PINS, 8 15/16" SHOULDERS	1	
15WX-15	HOUSING LOCK BOLT AND NUT	1	
40PGIR-16JE-LP	SPINDLE, LONG, W / 3 1/2" IF (MOD) LH PIN	1	
40PGIR-18	PACKING BOX	1	
40PGIR-18A	BOLTS W/WASHERS, PACKING BOX	4	
40PGIR-19	PACKING GLAND	1	
5JW-20	PACKING SET	OPTION	
5JW-20-416	PACKING SET, LOW PRESSURE	1	
5JW-21	LANTERN RING	1	
40PGIR-23	PACKING ADJUSTING GLAND	1	
40PGIR-24	ADJUSTING SCREW WITH NUT	2	
40PGIR-25	WASHPIPE	1	
OR-339	O-RING, WASHPIPE	1	
OR-343	O-RING, THREAD SEAL	1	
OR-344	O-RING, PACKING GLAND	1	
OR-346	O-RING, PACKING GLAND	1	
OR-350	O-RING, PACKING BOX	1	
40PGIR-70WT	WEAR TUBE	OPTION	

Other sizes of connections available, please consult factory.

Option for above swivel, may affect pricing of complete swivel. Other options available, please consult factory. 74

