

8.0PE SIDE INLET “SPECIAL SWIVEL”



- 6" Fluid passage
- Can be used for internal and external air lines
- For air-lift drilling but adaptable for all forms of drilling
- Large capacity tapered roller bearings for stem stability
- Grease lubricated packing and bearings
- Sealed bearing case

TECHNICAL DATA

LENGTH	WIDTH	WEIGHT	UPPER CONN.	HOSE CONN.	LOWER CONN.	FLUID PASSAGE	WORKING PRESSURE
28"	14 1/2"		OPTION	TO 6"	OPTION	MAX 6"	TO 1000 PSI

PARTS LIST

PART NUMBER	DESCRIPTION	NUMBER REQ.	
8.0PE-4075-XX	WESTERN SIDE INLET, 6" ID FLUID PASSAGE, TO 8" OD "CUSTOMER" SPECIFIED UPPER CONNECTION, 2" NPT FEMALE HOSE CONNECTION, WITH "CUSTOMER" SPECIFIED FLANGED LOWER CONNECTION		
8.0PE-01	STEM, 6WC LH BOX BY SPECIAL PIN	1	
8.0PE-01F-X	LOWER FLANGE	1	
8.0PE-04	PACKOFF HOUSING	1	
8.0PE-06	PACKING GLAND	2	
8.0PE-08	WEAR SLEEVE	2	
8.0PE-09	BEARING HOUSING	2	
8.0PE-10	PACKING SEAT RING	2	
8.0PE-20	PACKING SET	2	
8.0PE-70	INNERTUBE	1	
6CRCW-24	BEARINGS (CUP AND CONE)	2	
30NV-19	SEAL	2	
7.5LWW-54	LANTERN RING	2	
5.0DJ-10	SEAL	2	
OR-453	O RING	2	
OR-260	O RING	4	
OR-262	O RING	1	

Other sizes of connections available, please consult factory.

Option for above swivel, may affect pricing of complete swivel. Other options available, please consult factory.

